

BUILDERS BUTT®

PREMIUM CONSTRUCTION ADHESIVE

TECHNICAL DATA

+44 (0)7797 939988

sales@buildersbutt.com

www.buildersbutt.com

BUILDERS BUTT®

- Hybrid Polymer Adhesive
- Extremely high strength
- Excellent adhesion to most building materials
- Very high initial bonding strength ('high tack')
- Bonds without primer
- Can be applied to dry & slightly damp surfaces
- Suitable for dry & humid weather conditions
- High resistance to UV
- Permanent elasticity
- Good resistance to finger picking after curing
- Paintable with most water & solvent based paints
- Does not cause any corrosion in metal joints
- Solvent, isocyanate & phthalate free
- Suitable for Automotive & Marine use

DIRECTIONS FOR USE

- Ensure surfaces are clean of grease & dust.
- Cut the cartridge seal & screw on the nozzle
- Cut nozzle to the required size.
- Use a Skellington gun to apply.
- Skin formation time: 30 minutes.
- Approximate cure time: 24 hours.

BUILDERS BUTT®

WHITE



ALWAYS TEST BEFORE USE.

Not suitable for Polycarbonate or PE, PP, PE and Teflon® or for materials permanently immersed in water. Store in cool dry conditions between +5°C and 25°C. Shelf life: 12 months from manufacture. Contains: EUH 208 / Trimethoxyvinylsilane. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Safety Data Sheet available on request. For TDS please check website.



PREMIUM CONSTRUCTION ADHESIVE



EXTREMELY STRONG



HIGH TACK & FAST CURING



INTERNAL & EXTERNAL USE



UV & WEATHER RESISTANT

290 ml e

buildersbutt.com

CHARACTERISTICS



- Hybrid Polymer Adhesive
- Extremely high strength
- Excellent adhesion to most building materials
- Very high initial bonding strength ('high tack')
- Bonds without primer
- Can be applied to dry and slightly damp surfaces
- Suitable for dry and humid weather conditions
- High resistance to UV
- Permanent elasticity
- Good resistance to finger picking after curing
- Paintable with most water and solvent based paints
- Does not cause any corrosion in metal joints
- Solvent, isocyanate and phthalate free
- Suitable for Automotive and Marine use

APPLICATIONS

- Gluing of wooden & plastic laths, ornaments, frames, doorsteps, window sills, skirting boards, roofing elements, flooring...
- Bonding automotive & marine materials (not permanently submerged in water).
- Gluing of panels and elements in interior and ceiling construction: wall cladding elements and ceiling panels (interior), isolation panels (mineral wool, wood-wool cement & plastic foams, PUR, PIR, PS).
- Bonding and installation of laminated glass in the banking industry, miter of aluminium windows, mirrors, window and door frames, cable trays...
- Secure environments (i.e. prisons, hospitals...) where the sealant is hard so it can't be picked out by hand. Not for external glazing applications.
- Indoor and outdoor use.
- Bonding and assembling everything.

TECHNICAL CHARACTERISTICS

Type of product	Hybrid polymer
Number of components	1
Application temperature	+5°C - +40°C
Temperature resistance	-40°C - +90°C
Density: ISO 1183 (g/ml)	1.56
Curing system	Cross-linking by air humidity
Curing speed at 23 degrees C and 50% R.H. (mm, after 24h)	2.5 - 3
Skin forming time at 23°C and 50% R.H. (min.)	17
Shore A hardness: ISO 868	60
Maximum permissible deformation: ISO 11600	20%
Modulus at 100% elongation: ISO 8339 (N/mm ²)	1.6
Modulus at break: ISO 8339 (N/mm ²)	1.7
% Elongation at break: ISO 8339	110
Dry matter content	±100%
Shelf life of unopened product	12 months

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply

Storage conditions

Store in a dry, cool place at +5°C to +25°C. Keep out of direct sunlight.

PACKING AND COLOURS

25 x cartridge 290ML/box - 1200 pieces/pallet

White

METHOD OF USE

Preparation

- The surface must be solid, strong enough, clean, dust free and also free from grease. The surface doesn't need to be totally dry.
- If needed, degrease the materials to be glued with Builders Butt Wipes, appropriate cleaning agent, MEK, Multi-Purpose Super Cleaner, alcohol, ethanol.
- Use in well-ventilated rooms. Good ventilation is important during application and curing of the product.
- The user needs to make sure that the product is suitable for the application, always test before use. Consult our technical service if necessary.

Application

- Good ventilation is important during application and vulcanisation of the product.
- Apply Builders Butt Premium Construction Adhesive with the supplied nozzle in strips or dots to the base or on the element to be bonded. The strips must be applied in vertical rows. Apply the strips parallel to each other, to allow the humidity to reach the adhesive between the strips.
- Bring together the parts to be joined as quickly as possible, at least within 10 minutes (this depends on the temperature and relative humidity level). The parts can at this stage still be adjusted
- Finally, push down one over the other well or tap with a rubber hammer.
- It is advised to have a gap of 3.2 mm between the parts to be bonded spacer blocks or pieces of foam tape may be used), to allow the adhesive to smooth out any distortions (especially important in exterior use or under humid conditions).
- The internal strength of Builders Butt Premium Construction Adhesive immediately after application is such that bonding is possible without clamping or temporary support.

Cleaning

- After curing remove mechanically
- Any adhesive that may protrude along the edges can be removed using a stopping knife. Adhesive residue that has not yet dried, can be removed using Builders Butt Wipes, appropriate cleaning agent, Multi-Purpose Super Cleaner.

Paintable

- Paintable after curing with most water and solvent based paints. Curing time depends on the joint dimensions.
- After 48 hours, the surface must be cleaned first before it can be painted.
- Given the wide variety of paint types available, it is recommended that you test the compatibility of the sealant/adhesive with the paint in advance.
- Alkyd paints might require an extended drying time.

SAFETY

Consult the safety information on the packaging and the safety data sheet for more information.

LIMITATIONS

- Not suitable for permanent submersion.
- Not suitable for use on butiminous surfaces.
- Not suitable for use on PE,PA,PP,PTFE (Teflon).
- Not suitable for use on polyacrylate and polycarbonate.
- Not suitable for certain sanitary applications (not mould resistant).
- Not suitable for contact with edge sealing of insulating glazing. Avoid direct contact.
- Compatible with most PVB films of laminated glass. However, due to the large number of systems on the market and because the composition of it can be changed, this does not guarantee compatibility on all glazing sealants.
- Not suitable for bonding masonry to lintels.

TECHNICAL APPROVALS

- GEV Emission EC1plus label: very low VOC emissions
- French VOC emission class A+
- IKI-report for the use in hospitals as glue and adhesive for wall panels.





DISCLAIMER

This disclaimer is issued by Builders Butt Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS").

Please read this disclaimer carefully before using any of the Products. Using this TDS and / or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department.

This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue.

Destroy all previous TDS, and if in any doubt, contact the Company, quoting the product details.

Builders Butt Limited
Unit 7 Sion Hall Farm
La Rue St Thomas
St Saviour
Jersey
JE2 7SS
Channel Islands