

## F594C Carpet Tile Tackifier Spray Adhesive

**Versatile tackifier adhesive** for release bonding of **carpet tiles**.

- **Permanently** tacky
- **Tiles** can be **lifted** and **relaid**
- **Superfast** spray **action**
- **Fast** drying
- **Excellent** coverage

### Description:

F594C Carpet Tile Tackifier Spray Adhesive is a versatile one part synthetic rubber/resin adhesive specially formulated to remain tacky for the super quick installation of carpet tiles, that can be subsequently uplifted and re-laid.

### Uses:

F594C Carpet Tile Tackifier Spray Adhesive is suitable for the release bonding of carpet tiles with bitumen/felt backings, underlays including PU Foam and Crumb Rubber.

### Subfloors:

F594C Carpet Tile Tackifier Spray Adhesive is suitable for bonding to concrete bases, cement screed, smoothing & levelling compounds, thermoplastic tiles, flooring grade chipboard, hardboard, plywood, stone, terrazzo, quarry tiles, ceramic, rigid steel. Especially suited for raised access panels.

Not suitable for polyurethane or highly plasticised PVC floorcoverings.

### Specification:

Adhesive Type:	Synthetic Rubber / Resin
Colour:	Light Beige
Flashpoint:	Highly Flammable
Coverage:	Approxiamtely 300-500m <sup>2</sup> per 19.5L canister
Application Temperature:	+5°C - +30°C
Working/ Drying Time:	Approx. 10 minutes to 2 hours, as long as surfaces do not get contaminated.
Storage & Shelf Life:	12 months in original, unopened container stored between +5°C and +30°C.
Container Size:	19.5 L Canister



### Directions for Use:

#### IMPORTANT

Before using F594C Carpet Tile Tackifier Spray Adhesive please refer to the safety guide and data sheet available at [www.floorwise.co.uk](http://www.floorwise.co.uk)

All phases of the installation should comply with the latest editions of the following standards:

- BS 8102 Code of Practice for the protection of buildings against water from the ground.
- BS 5325 Code of Practice for the installation of textile floorcoverings.
- BS 8203 Code of Practice for the installation of resilient floorcoverings.

### Preparation:

All surfaces to be bonded must be clean, dry and free from rising damp, grease, dust or any other loose material. Cementious surfaces should have a relative humidity of less than 75%RH. Underfloor heating should be switched off 48 hours before and after application, the gradually increased after this period. Before installation all materials should be conditioned to room temperature. Application temperature should be between +5°C and +30°C.

It is advised to always test a sample of the materials to be bonded for product compatibility and ensure that the spray gun is correctly adjusted by test spraying on a practice piece.

## Application:

Hold the gun at right angles, 10 - 20cm above the surface and apply a generous, but uniform coating to the whole area. Paying particular attention to the edges.

Do not allow the adhesive to puddle or concentrate in one area, double coating is recommended for porous surfaces.

Allow time for the solvents to evaporate. The adhesive should be touch dry and very tacky before laying the carpet tiles. Never lay the tiles too early as solvent can get trapped causing air bubbles &/or a permanent bond may occur.

Under normal conditions the adhesive dries in a few minutes. High humidity and low temperatures will slow drying time.

Once ready press the surfaces firmly together from the centre outwards to ensure good contact is made over the whole area. Unless the manufacturer recommends otherwise, roll in both directions with a 60-75kg roller to ensure good transfer of adhesive.

For vertical applications, apply pressure with a paperhanger's roller or spatula.




## Cleaning:

Remove any overspray immediately with Floorwise solvent cleaner or the minimum of white spirit.

**DO NOT USE SOLVENTS TO CLEAN THE SKIN.**



## Safety Guidance:

<b>DANGER</b>	<b>F.594C Carpet Tile Tackifier</b>	<b>UN3501</b>
  	<b>Contains: PENTANE, ACETONE</b>	
	<p><b>Hazard Statements</b>  Extremely flammable aerosol.  Pressurised container: may burst if heated  May cause drowsiness or dizziness.  Toxic to aquatic life with long lasting effects.</p> <p><b>Precautionary Statements</b>  Keep away from heat/sparks/open flames/hot surfaces.  No Smoking  Do not spray on an open flame or other ignition source.  Pressurised container: Do not pierce or burn, even after use.  Use only outdoors or in a well-ventilated area.  Wear protective gloves/protective clothing/eye protection/face protection.  Protect from sunlight. Do not expose to temperatures exceeding 50°C.  Repeated exposure may cause skin dryness or cracking.</p> <p><b>KEEP OUT OF REACH OF CHILDREN</b></p> <p>Dispose of contents/container in accordance with national regulations</p> <p>A full materials safety data sheet relating to this product is available at <a href="http://www.floorwise.co.uk">www.floorwise.co.uk</a></p>	
<b>19.5L</b>		
Label in accordance with (EC) No. 1272/2008		

This product data sheet is provided for guidance only. For further information and advice on application, or if in any doubt as to the suitability of the product for the installation, please contact our Technical Department for advice.